



# CUSTOM TAPE LTD

Farington Mill, Centurion Industrial Estate,  
Centurion Way, Leyland, PR25 4GU

T: 01772 434444 E: sales@customtape.co.uk



## SPECIFICATION SHEET

### Vinyl PVC Tape

High tensile strength and stability / high immediate tack and adhesion on various surfaces / smooth and low noise unwinding / low elongation / moisture resistant / resistant to diluted acids and alkalis / temperature resistant: after application at room temperature from approx. - 20°C up to +70°C short term / printable / suitable for recycling processes.

### TECHNICAL DATA

Backing:	PVC (Polyvinylchloride)
Adhesive:	Natural Solvent Rubber
Tensile Strength:	N/25mm (minimum 90)
Thickness of backing:	0.052 +/-10%
Thickness of adhesive:	0.02 +/- 10%
Adhesive force on steel:	cn/25mm 500-150
Temperatures:	-20°C to 70°C
Base Colour:	Clear, White, Havana Brown
Ink:	Highly resistant, solvent based
Core:	76mm diameter cardboard core
Elongation:	>165%
Tolerance:	As per our current house standards +/- 10%

Low Noise	***	Resistant to diluted acids & alkalis	**
Tensile strength (breaking load)	**	Resistant to humidity	**
Immediate tack	***	Elongation	**
Adhesion (to steel)	***	Removeable residue-free	*
For smooth services	**	Die cutting	**
For different services	**	Machine rolls	***
Easy & smooth unwinding	***	Carton sealing	**

**THE ABOVE SPECIFICATION IS MANDATORY AND CAN ONLY BE ALTERED WITH THE WRITTEN AGREEMENT OF THE SUPPLIER**

Complies with ENA TS 12-23 Issue 3 2013

BS EN 12613: 2009 Date: 28/11/2019